

Outdoor Motion Tracking Infra Red High Speed PTZ Camera--100Meters SE325iA



Feature: Automatic Motion detecting and Tracking with virtual alarm line featured, aluminum shell with wiper equipped OSD, privacy mask (subject to camera function),256 Camera ID address, pattern tour 40 Seconds 360°continuous pan, 90°tilt, 180°flip, 6 cruising tracks, 16 presets each track, 128 presets totally, shuttle scan RS485 or GSM, multi-protocol, 12VDC **Vehicle** package , alarms 4 in 1 out (24V type), camera position display



Model	SE325iA-27x	SE325iA-30x	SE325iA-480	SE325iA-980	SE325iA-1010	SE325iA-26X	SE325iA-22X	SE325iA-200
Image Sensor	1/4 Sony Exview HAD							
Total Pixels	P795x596N768x494 811x508		P795x596N768x494 P795x596N768x494 P795x596N768x494 P795x596N768x494 P795x596N768x494 P795x596N768x494					
Synchronization	Internal							
Video Out	1.0Vp-p (75 OM, composite)							
White Balance	5 steps Auto/ Push auto/ Outdoor/ Indoor/ Special							
Scanning frequency	Horizon: 15.625k HZ , Vertic: 50 HZ							
Horizontal resolution	480TVL	540TVL	540TVL	540TVL	540TVL	480TVL	480TVL	470TVL
S/N Ratio	>48dB	>48dB	>50dB	>50dB	>50dB	>48dB	>48dB	>48dB
Electric Shutter (S)	1/50-10000	1/50-10000	1-1/10000	1-1/10000	1-1/10000	1/50-10000	1/50-10000	1/50-10000
Min. Illumination	0.001Lux	0.001Lux	0.01Lux	0.01Lux	0.01Lux	0.01Lux	0.001Lux	0.1Lux
BLC	9 Zones	9 Zones	9 Zones	9 Zones	9 Zones	Auto	Auto	Auto
Focal Length	f3.6-97.2mm	f3.3-99mm	f4.1-73.8mm	f3.5-91mm	f3.4-122.4mm	f3.5-91	f3.9-85.8	f3.9-85.8
Max. Zoom	270X	300X	216X	312X	432X	260X	220X	352X
Camera OSD	ON/OFF	ON/OFF	NO	NO	NO	ON/OFF	ON/OFF	ON/OFF
Gain	Auto/Manu							
Pan preset speed	120°S							
Tilt preset speed	80°S							
Pan speed	80°S							
Tilt speed	60°S							
Pan range	360°continuously endless							
Tilt range	90°, 180°auto flip							
Preset &. Track	128 presets, 6 tracks, 40 seconds pattern memory; automatic motion detecting and tracking							
Communication	RS485, Cat5 cable, Multi-protocol supported							
Privacy Masking	NO	NO	YES	YES	YES	NO	NO	NO
WDR	NO	NO	NO	NO	YES	NO	NO	NO
DSS &. SensUp	YES	YES	NO	NO	anti shack	NO	YES	NO
Working Environment	negative 35°C to 50°C ; humidity 95% without agglomeration							
Weight &. Power	10Kg; 24VAC, 20VA or Vehicle 12VDC, 3.5VA							