

Outdoor Laser High Speed PTZ Camera--400Meters

SE325L



Feature: Laser range up to 400 meters, perfect night vision, Weather proof, Aluminum shell, IP66
 Shock proof, proper car surveillance, 360°continuous pan, 180°blind less tilt, OSD, 6 privacy masks, 4 alarms in 1 out
 6 cruising tracks, 16 presets each track, total 128 presets, camera position (angle) display, 1 shuttle scan
 24VAC local power optional, camera wiper equipped



Model	SE325L-271	SE325L-375	SE325L-927	SE325L-980	SE325L-1010	SE325L-276	SE325L-226	SE325L-858
Image Sensor	1/4 Sony Exview HAD							
Total Pixels	P795x596N768x494 P795x596N811x508 P795x596N768x494 P795x596N768x494 P795x596N768x494 P795x596N768x494 P795x596N768x494 P795x596N768x494							
Synchronization	Internal							
Video Out	1.0Vp-p (75 OM, composite)							
White Balance	5 steps Auto/ Push auto/ Outdoor/ Indoor/ Special							
Scanning frequency	Horizon: 15.625k HZ , Vertic: 50 HZ							
Horizontal resolution	550TVL	550TVL	540TVL	540TVL	540TVL	480TVL	480TVL	540TVL
S/N Ratio	>48dB	>48dB	>50dB	>50dB	>50dB	>48dB	>48dB	>48dB
Electric Shutter (S)	1/50-10000	1/50-10000	1/50-1/10000	1-1/10000	1-1/10000	1/50-10000	1/50-10000	1/50-30000
Min. Illumination	0.001Lux	0.001Lux	0.001Lux	0.01Lux	0.01Lux	0.001Lux	0.001Lux	0.1Lux
BLC	9 Zones	9 Zones	9 Zones	9 Zones	9 Zones	Auto	Auto	Auto
Focal Length	f3.6-97.2mm	f3.5-129.5mm	f3.25-88mm	f3.5-91mm	f3.4-122.4mm	f3.6-97.2mm	f3.9-85.8mm	f3.6-82.8mm
Max. Zoom	27x12=324X	37x12=444X	27x12=324X	26X12=312X	36x12=432X	27x10=270X	22x10=220X	23x12=276X
Special Function	SSNR II, DIS	WDR, SSNR II	DSS,3D-DNR	OSD, Masking	WDR, DSS	DSS,TDN	DSS,TDN	WDR, FNR
Gain	Auto/Manu							
Pan preset speed	120°S							
Tilt preset speed	80°S							
Pan speed	80°S							
Tilt speed	60°S							
Pan range	360°continuously endless							
Tilt range	90°, 180°auto flip							
Preset &. Track	128 presets, 6 tracks, 40 seconds pattern memory							
Communication	RS485, Cat5 cable, Multi-protocol supported							
Privacy Masking	NO	NO	YES	YES	YES	NO	NO	NO
Working Environment	negative 35°C to 50°C ; humidity 95% without agglomeration							
Weight &. Power	10Kg; 24VAC, 20VA							